


Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 LRFP 10/W TR IM
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PU	PU	Impregnated fabric	
Thickness:	1		-	mm (approx.)
Colour:	White	White	-	
Hardness:	92 Shore A		-	
Profile:	-		-	

Total thickness:	3,5	mm (approx.)
Weight:	3,1	kg/m² (approx.)
Max. width:	2000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	9	N/mm
Advised pretension:	4 - 7	N/mm
Maximum allowable tension:	12	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:		
Flexing:	50	mm
Backflexing:	120	mm

Special approval: FDA, 10/2011/EC + amendments

Applications: Conveying of meat, fish and poultry products
Conveyor belt for the food industry
Oil and grease resistant